










Break Sharp Edges: 0,1 mm

Revision	Date	Description				
Engineered by: C. Woodson			Name:	Date:	Scale: 2 : 1	
		Designer:	Galba, J.	18/12/2010	SheetSize: A3	
		Approved:	Galba, J.	18/12/2010		
Project: P0003					Material: Stainless Steel	
Miniature Steam Engine					Total Mass: 0,007 kg	
Title: Vertical Steam Engine with Reverse Gear (anno 1830) Piston Ring 000.018						
 InventorWizard		Drawingnumber: P0003 - 000.018				Sheet: 0001
		Design State: Released				Drawing made with autodesk Inventor Revisions only permitted by CAD

Corresponding symbols																	
Roughness Classes (NBN 88-02) (ISO 1302)									N11	N10	N9	N8	N7	N6	N5	N4	
Roughness Value "Ra" in µm (NBN 88-02) (ISO 1302)									25	12,5	6,3	3,2	1,6	0,8	0,4	0,2	

Allowable deviations for dimensions without tolerance indication (machined surfaces)

For measurements (deviations in mm)									Filletts and chamfers					Angles (in ° and ')				
Accuracyclass (ISO 2768.1)	Dimensions in mm								Dimensions in mm					Length of the shortest leg				
	0,5	>3	>6	>30	>120	>400	>1000	>2000	0,5	>3	>6	>30	>120	to 10	>10	>50	>120	above 400
	to 3	to 6	to 30	to 120	to 400	to 1000	to 2000	to 4000	to 3	to 6	to 30	to 120	to 400					
f Fine	±0,05	±0,05	±0,1	±0,15	±0,2	±0,3	±0,5	±0,8	±0,2	±0,5	±1	±2	±4	±1°	±30'	±20'	±10'	±5'
m Medium	±0,1	±0,1	±0,2	±0,3	±0,5	±0,8	±1,2	±2										
c Rough	±0,2	±0,3	±0,5	±0,8	±1,2	±2	±3	±4	±0,4	±1	±2	±4	±8	±1°30'	±1°	±30'	±15'	±10'
v Very Rough	–	±0,5	±1	±1,5	±2,5	±4	±6	±8										

This document is for educational purposes only and property of Inventor Wizard. It shall not without our permission be altered, copied, used for manufacturing or communicated to any other person or company.

