



Break Sharp Edges: 0,1 mm

Revision	Date	Description				
Engineered by: C. Woodson			Name:	Date:	Scale: 5:1	
		Designer:	Galba, J.	18/12/2010	SheetSize: A3	
		Approved:	Galba, J.	18/12/2010		
Project: P0003					Material:	Steel
Miniature Steam Engine					Total Mass: 0,002 kg	
Title: Vertical Steam Engine with Reverse Gear (anno 1830) Reverse Gear Link Stud 000.033						
 InventorWizard.be/.nl		Drawingnumber: P0003 - 000.033				Sheet: 0001
		Design State: Released				Drawing made with autodesk Inventor Revisions only permitted by CAD

Corresponding symbols										▽	▼	▽▽	▼▼	▽▽▽	▼▼▼				
Roughness Classes ( NBN 88-02 ) ( ISO 1302 )									N11	N10	N9	N8	N7	N6	N5	N4			
Roughness Value "Ra" in µm ( NBN 88-02 ) ( ISO 1302 )									25	12,5	6,3	3,2	1,6	0,8	0,4	0,2			
Allowable deviations for dimensions without tolerance indication (machined surfaces)																			
For measurements ( deviations in mm )									Fillet and chamfers					Angles ( in ° and ' )					
Accuracyclass (ISO 2768.1)	Dimensions in mm								Dimensions in mm					Length of the shortest leg					
	0,5 to 3	>3 to 6	>6 to 30	>30 to 120	>120 to 400	>400 to 1000	>1000 to 2000	>2000 to 4000	0,5 to 3	>3 to 6	>6 to 30	>30 to 120	>120 to 400	to 10	>10 to 50	>50 to 120	>120 to 400	above 400	
	f Fine	±0,05	±0,05	±0,1	±0,15	±0,2	±0,3	±0,5	±0,8	±0,2	±0,5	±1	±2	±4	±1°	±30'	±20'	±10'	±5'
	m Medium	±0,1	±0,1	±0,2	±0,3	±0,5	±0,8	±1,2	±2										
	c Rough	±0,2	±0,3	±0,5	±0,8	±1,2	±2	±3	±4	±0,4	±1	±2	±4	±8	±1°30'	±1°	±30'	±15'	±10'
v Very Rough	-	±0,5	±1	±1,5	±2,5	±4	±6	±8											

This document is for educational purposes only and property of Inventor Wizard.  
It shall not without our permission be altered, copied, used for manufacturing or  
communicated to any other person or company.